



TZT 10



SPECIFICATIONS

DESCRIPTION	UNIT	III	IV
Vehicle Speed (Max.)	mph	9 -11	9 -11
Tire Size	Inch	20 -23	20 -23
Max Vehicle Weight w/ attachment and operator	lbs	1700	1700
Reduction ratio		20.48 : 1	20.48 : 1
Pump & Motor Displacement	cc / rev	10 / 10	10 / 10
Brake Capacity	N-m	439	439
Brake Arm Torque	N-m	21.2	21.2
Rated Axle Torque	N-m	274	274
	Break	Wet Disk, Internal	Wet Disk, Internal
	Gears	PM & Steel	Steel
	Bearings	Special	Special
	Valve Plates	Standard	Standard
	Charge Pump	Rigid (Changeable Filter)	Rigid (Changeable Filter)
	Auxiliary Port	Optional	Optional
	Return to Neutral	Optional (Outboard)	Optional (Outboard)
	Installed Reservoir	Optional	Optional
	Fan & Pulley	Optional	Optional
	Fan Size	7"	7"
	Pulley Size	4.5" or 5"	4.5" or 5"
	Pulley Height		
	from axle center	Min.110mm	Min.110mm
	Wheel Hub	Optional	Optional
	Control Lever	Optional (In/Outboard)	Optional (In/Outboard)
	Auxiliary Ports	Optional	Optional
	Max Pressure	4.5MPa	4.5MPa
	Flow	4.125cc/rev	4.125cc/rev